

Installation instructions:

AKRAPOVIC SLIP-ON SP SERIES EXHAUST SYSTEM – ADDITIONAL FITTING SET for the APRILIA PEGASO STRADA 650 (2005-)

Congratulations on purchasing an Akrapovic exhaust system. Please read these installation instructions carefully. If you have any trouble installing the system please contact your authorized dealer!

IMPORTANT INFORMATION

Exclusion of Certain Liability

1. The manufacturer, importer or dealer shall not be liable for any incidental damage including personal injury or any other damages caused by improper installation or operation of the Akrapovic exhaust system. When installing the Akrapovic exhaust system be careful that the exhaust system does not touch other parts sensitive to high temperature.
2. Akrapovic makes no representation or warranties with regard to damage caused by the improper installation, use and maintenance of the Akrapovic exhaust system. The warranty is limited to defects recognized by our technical department and to normal use, and excludes items subject to normal wear (gaskets and damping wool). The guarantee is void in case of accident, modification, improper or competition use.
3. Do not attempt to install the Akrapovic exhaust system on a motorcycle for which it was not made or tested by Akrapovic.
4. When the exhaust system gets very hot during operation, be careful not to burn yourself on the exhaust system or parts which are in direct contact with it, even when the motor is not running. Also protect other people, especially children, from the injuries mentioned above.
5. In some cases Akrapovic exhaust system kits contain chemical products (ceramic anti-seizing grease; bolt sealant). Handle with care, do not inhale or swallow. Avoid excessive contact with skin, eyes or mucous membranes. Keep out of reach of children.
6. Technical specifications of Akrapovic exhaust systems and related products subject to change without notice.

Trademarks

The Akrapovic Exhaust System Technology logo is a registered trademark of Akrapovic d.d.

Akrapovic website

Information about Akrapovic exhaust systems and related products is available on the Akrapovic website at:
<http://www.akrapovic.com/>

Copyright

No part of the Akrapovic exhaust system or its documentation may be reproduced or distributed in any form or by any means without the prior written authorization of the Akrapovic company.

© Akrapovic, d.d. All rights reserved.

Symbols

The following symbols are used throughout these installation instructions:




INSTALLATION INSTRUCTIONS

 **BEFORE INSTALLING CHECK SCHEMATIC OF THE EXHAUST SYSTEM!**

! IF ANY ITEMS IN THE AKRAPOVIC EXHAUST SYSTEM PACKAGE ARE MISSING PLEASE CONTACT YOUR AUTHORIZED DEALER. KEEP THE SCHEMATIC FOR FUTURE REFERENCE.

! THESE INSTALLATION INSTRUCTIONS MUST BE READ CAREFULLY IN ORDER TO ENSURE PROPER INSTALLATION AND OPERATION OF THE AKRAPOVIC EXHAUST SYSTEM.

! THE EXHAUST SYSTEM CAN BE EXTREMELY HOT. ALLOW THE MOTORCYCLE TO COOL DOWN BEFORE BEGINNING INSTALLATION.

 **WE ADVISE YOU TO LEAVE INSTALLATION TO A QUALIFIED SERVICEMAN. IMPROPER INSTALLATION MAY RESULT IN A SHORTER LIFETIME OF THE EXHAUST SYSTEM AND/OR DAMAGE TO THE MOTORCYCLE.**

INSTALLATION OF THE ADDITIONAL FITTING SET FOR THE LEFT MUFFLER

When installing left muffler viewed from the rear it is necessary to use the additional fitting set!

WARNING:

The following installation instructions are intended only for installing additional fitting set for the right muffler, otherwise it is necessary to follow the procedure of the Akrapovic Installation instructions No. NAV-192 for the Akrapovic Slip-On SP Series exhaust system for the Aprilia Pegaso Strada 650 (2005-).

1. correctly position and install onto the lower header tube additional metal ring (longer bracket for attaching the spring) (**Figure 1, 2**)
2. hand tighten the bolt of the additional metal ring (**Figure 3**)
3. install additional graphite gaskets into the link pipe of the left muffler (NAV-192)
4. coat the bolt and interior side of the metal clamp with Akrapovic anti-seize lead-free copper paste (black tube) (NAV-192)
5. correctly position and install the metal clamp onto the link pipe (NAV-192)
6. position the left muffler with welded link pipe correctly and slide it onto the outlet side of the lower header tube (**Figure 4**)
7. to assure adequate tension of the spring position the additional metal ring again and tighten fully the bolt of the additional metal ring for attaching spring (**Figure 3**)
8. attach the long sized spring (for the left muffler) at the link pipe – header tube joint (**Figure 5**)
9. proceed with the installation according to the installation instructions No. NAV-192

Check the operation of the brakes and suspension. Make sure all the bolts are sufficiently tightened. In case the exhaust system touches the cowling or other parts repeat the adjustment of the exhaust system or contact your authorized dealer.

! IT IS NORMAL IF WHITE SMOKE COMES OUT OF THE MUFFLER ON FIRST OPERATION.

! DO NOT STAND BEHIND THE MUFFLER ON FIRST OPERATION.

! DO NOT USE AUTOMOTIVE WHEEL CLEANERS OR ANY CLEANING PRODUCTS WHICH CONTAIN ACIDIC ADDITIVES TO CLEAN AKRAPOVIC EXHAUST SYSTEMS.

Photos:



Figure 1



Figure 2



Figure 3



Figure 4



Figure 5